

TECHNICAL DATA DARANÀ

Issued on 06/05/2015 - Rev. n. 1 del 05.06.2022

Product features:

Daranà is NOT a painting and as such it does not appear on the market with the traditional packaging in a jar typical of a decorative product, it is an absolute innovation in the field of decoration that allows you to reproduce a metal effect in liquid form, its innovative structure allows you to decorate any type of surface, walls, ceilings, furniture, furnishing accessories can be enriched with a simple gesture!

DARANÀ is the combination of science and innovation.

Preparation of the base:

On well-consolidated, perfectly smooth substrates, apply a layer of PanareaStone to create the desired texture, leave to dry for at least 12 hours (see PanareaStone technical data sheet).

Application method:

Proceed with the drafting of Decor Fix (adhesion promoter) using a brush along the entire length of the surface and about 20 cm in width, immediately afterwards apply Daranà over the still fresh Decor Fix and with the help of a damp cloth smooth the filler which contains the Daranà, proceed with this system for the entire surface to be treated. After 3/4 hours, remove the filler that holds Daranà, wait about 6/8 hours and proceed with the application of a single layer of ProteKto EcoSilan using a brush and taking care to follow the previously created texture, let the product rest for about 10/20 minutes (times may be longer or shorter depending on the environmental and/or seasonal temperature), and gently clean the surface using a soft cotton cloth.

Useful tips:

Do not touch Daranà with your hand before the protective one, the metals that make up the product could alter and damage the surface. Do not apply Daranà on lime-based or still damp products, the product could wrinkle, crack, form strips or lift from the support.

Technical data:

Yield Daranà: 18 m²

Daranà size: 15X122 mt

Color: Stainless steel and Gold

Kit packaging: 1 Daranà + 1 Decor Fix lt 2,5

Do not apply the product at temperatures below +5 °C and above +35 °C.

- *The data contained may vary at any time without prior notice by Nikkolor Italia.*
- *The information contained in these technical data sheets are the result of our best knowledge and, as such, are disclosed for information purposes, therefore it does not engage the responsibility of our Company towards any disputes arising from conditions of use that are beyond our control, who intends to use it is required to establish whether the product is suitable for use.*
- *Our The guaranteed obligation is therefore limited to the quality and constancy of the same in relation to the finished product, and exclusively for the above data.*
- **For more detailed information, please contact our TECHNICAL ASSISTANCE service**

