

TECHNICAL DATA EMOTIONS

Issued on 03/12/2013 - Rev. n. 1 of 26.01.2021

Employment characteristics:

Decorative non-toxic, non-yellowing decorative wall covering, permeable to water vapor, perfumed during application, resistant to fungi and bacteria. Thanks to its elegant chromatic finish, EMOTIONS is used in prestigious environments both private and public. EMOTIONS combines the preciousness of the silk effect with the softness of the soft touch textures created.

Composition:

Special acrylic emulsion mixes of natural biostable micas, ceramic microspheres, various pigments, and additives.

Fund preparation:

On well-consolidated substrates, perfectly smooth and painted with white or colored washable water-based paint, the application does not require any primer, alternatively apply two coats of white or colored PRIMER PLUS.

Applications:

Spatolato effect: apply a first layer of EMOTIONS using a plastic spatula and let the product dry for at least 6-8 hours. Apply a second layer of EMOTIONS in small sections of about 1 square meter and then straighten in several directions. Repeat for all the surface to be covered.

Macramé effect: apply a first layer of EMOTIONS using a plastic trowel and leave to dry for at least 6-8 hours. Apply a second layer in small strokes for about 1 square meter and then smooth the surface with circular movements. Repeat for the entire surface to be covered as the first layer.

TECHNICAL DATA:

SPECIFIC WEIGHT: 0.700 Kg./Lt. +/- 5%

COLOR: colors of colorable folder through our tinting system Color tinting system 3.0

VISCOSITY: thixotropic appearance

Spatolato effect: 4 m² / Lt. two-handed depending on the absorption of the support.

Macramé effect: 5 m² / Lt. two-handed depending on the absorption of the support.

DILUTION: ready to use

PACKAGING: polyethylene containers of 2.5 liters

DRYING: to the touch 2 h, in depth 24h to 20 ° C

APPLICATION: plastic trowel, brush, spalter

STORAGE: in original sealed packaging and in a dry place between + 5 ° C and + 30 ° C.

PERMEABILITY TO WATER STEAM: high UNI 10795 UNI EN ISO 7783-2

RESISTANCE TO ALCALS: resistant to alkali UNI 10795

DIRT TANK: low UNI EN 10792

Conforming to the UNI EN 15457 standard (resistance to the growth of fungi), due to the presence of specific additives with a broad spectrum of action, it allows the product to prevent the formation of mold, fungi, algae, and moss over time.

N.B. THE COLORINGS OF EMOTIONS ARE REPRODUCIBLE BY OUR TINTOMETRIC SYSTEM IN THE ITEM METALLIKA, IT IS RECOMMENDED TO HALF THE QUANTITY OF DYE COMPARED TO METALLIKA, WE SUGGEST BEFORE LAYING A TEST FOR THE RELIABILITY OF THE COLOR

The use of coloring pastes not supplied by Nikkolor Italia can compromise not only the aesthetic appearance but above all can significantly alter the performance of the product itself.

- The data contained may vary at any time without prior notice by Nikkolor Italia.
- The information contained in these technical data sheets are the result of our best knowledge and, as such, are disclosed for information purposes, therefore it does not engage the responsibility of our Company towards any disputes arising from conditions of use beyond our control, who intends to use it is required to establish whether the product is suitable for use.
- Our warranty obligation is therefore limited to the quality and constancy of the same in relation to the finished product, and exclusively for the data reported above.
- **For more detailed information, please contact our TECHNICAL ASSISTANCE service.**



