

## *Primer nk*

### **TECHNICAL DATA PRIMER NK**

Issued on 03/12/2013 - Rev. n. 1 of 26.01.2021

**Hooking Bridge high performance for construction surfaces to be coated.**

#### **DESCRIPTION:**

Primer NK is an ecological formulation based on water-based resins, siliceous aggregates, marble chips, inorganic pigments and specific additives that offers an exceptional high elasticity adhesion bridge, formulated for the application of Cemento 3D up to a thickness of up to 6 cm, applicable on any building support (concrete, plaster, tiles, bricks, plaster and plasterboard, stones, metal, glass, insulating panels, etc.). Primer NK guarantees an extraordinary adhesion to the coating to be applied to internal or external supports, even after a few months from the treatment.

#### **USE:**

PRIMER NK is used as an adhesion promoter before the application of Cemento 3D, MarmUra, PanareaStone, ArchiMetal, etc..., in some cases it is used before the application of Beton KA+KB.

#### **PREPARATION:**

The substrate to be treated must be clean and free of detached areas. A possible dustiness of the support must be removed to dry or wet. Apply on dry surfaces.

#### **PREPARATION OF THE PRODUCT:**

The product is ready for use but in certain cases it can be diluted 10/15% with water for a two-layer application.

#### **APPLICATION:**

Apply the product in a single coat by brush, roller or spray spreading it evenly over the entire surface and wait for the drying. After 12 hours, you can proceed to the desired overcoating.

#### **TECHNICAL DATA:**

Color: Transparent whitish

Appearance: Liquid

Specific gravity: 1.5 kg/lit

Solid content: 67%

Water solubility: soluble

Average consumption: 10 square meters with a 2.5 liter two-handed

Average thickness: 300 µ

Out of dust at 23 ° C ca.: 3 hours in outdoor humidity function

Time for the overlay coating: 12 hours

Flammability: Not flammable

Storage: 12 months at a temperature between +5°C and +35°C away from moisture of use temperature limits: +5°C / +35°C



Packaging: Lt 7 and Lt 2.5

Cleaning of tools: With clean water

**WARNINGS:**

Protect from frost.

Do not apply at temperatures lower than +5 ° C.

Do not use on hot surfaces or after long exposure to the sun.

Store in a dry place at a temperature between +5 ° C and + 35 ° C.

Irritating to eyes. In case of contact, wash thoroughly with water and if necessary, consult a doctor. Use latex gloves. Keep out of reach of children.

Do not disperse the container after use.

- *The data contained may vary at any time without prior notice by Nikkolor Italia.*
- *The information contained in these technical data sheets are the result of our best knowledge and, as such, are disclosed for information purposes, therefore it does not engage the responsibility of our Company towards any disputes arising from conditions of use beyond our control, who intends to use it is required to establish whether the product is suitable for use.*
- *Our warranty obligation is therefore limited to the quality and constancy of the same in relation to the finished product, and exclusively for the data reported above.*
- **For more detailed information, please contact our TECHNICAL ASSISTANCE service.**