

## TECHNICAL DATA VELATURA SILOSSANICA

Issued on 03/12/2013 - Rev. n. 1 of 26.01.2021

### FEATURES AND USES

semi-opaque finish for interiors and exteriors based on acrylic-siloxane emulsion, ancient decorative effect. Applicable both on smooth support that rough, either mineral or synthetic. Applied to the outside it allows to obtain a pleasing light colors dark antique effect that goes to embellish and protect the facade, guaranteeing an exceptional water repellency while maintaining unchanged the permeability of the media steam. Inside it can be applied guaranteeing a perfect washability and exceptional aggression bacterial resistance. Its flexibility decorative antique effect and its exceptional endurance performance rank VELATURA SILOSSANICA site as a product for facades in historic centers.

### COMPOSITION

Emulsion acrylic-siloxane, photostable pigments, additives.

### PREPARING THE SURFACE

Sanding, dusting, any imperfections with stucco in paste and / or powder form and apply a suitably diluted universal Fissativo with water according to the absorption of the substrate. Allow to dry for at least 4 hours and apply one or two coats of PRIMER PLUS white or slightly pigmented, suitably diluted, interspersed between a hand and the other at least 4-5 hours.

### APPLICATION

proceed with the drafting of VELATURA SILOSSANICA of the desired color with a brush, and quickly, product is still fresh, finish with wool glove with non-continuous circular movements.

### WARNINGS:

Do not apply on damp walls or where there has been ascertained rising damp, do not apply in foggy or near rains. Apply with a temperature between 5 and 30 ° C.

### TECHNICAL DATA

SPECIFIC WEIGHT: 1,040 +/- 5%

COLOR: as per folder

VISCOSITY ' : 200 " - 250" Ford Cup 4

YIELD: 9-10 m<sup>2</sup> / lt in one coat

DILUTION: ready for use

PACKAGE: polyethylene containers Lt. 2,5 - 1 Lt.

DRYING: tack free 1 h, in depth 24h at 20 ° C

TEMPERATURE OF APPLICATION: between 7 ° C and 30 ° C

APPLICATION: Brush, roller, or spray

STORAGE: 24 months in unopened packs away from temperature changes

**The use of coloring pastes not supplied by Nikkolor Italia can compromise not only the aesthetic appearance but above all can significantly alter the performance of the product itself.**

- The data contained may vary at any time without prior notice by Nikkolor Italia.
- The information contained in these technical data sheets are the result of our best knowledge and, as such, are disclosed for information purposes, therefore it does not engage the responsibility of our Company towards any disputes arising from conditions of use beyond our control, who intends to use it is required to establish whether the product is suitable for use.
- Our warranty obligation is therefore limited to the quality and constancy of the same in relation to the finished product, and exclusively for the data reported above.
- **For more detailed information, please contact our TECHNICAL ASSISTANCE service.**



